



27006-1/2

LED panel Ø 120mm 6 watt

ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	450
life time	50.000 hrs
beam angle	120 deg
wattage	6 watt
replacement for	2 x T1 60 cm
Ø diameter	120 mm
cut out	107mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands
T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



27009-1/2

LED panel Ø 148mm 9 watt

ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	700
life time	50.000 hrs
beam angle	120 deg
wattage	9 watt
replacement for	4 x T1 60 cm
Ø diameter	148 mm
cut out	133mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands

T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



27012-1/2

LED panel Ø 170mm 12 watt

ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	900
life time	50.000 hrs
beam angle	120 deg
wattage	12 watt
replacement for	4 x Tl 60 cm
Ø diameter	170 mm
cut out	155mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands

T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



27015-1/2

LED panel Ø 200mm 15 watt

ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	1100
life time	50.000 hrs
beam angle	120 deg
wattage	15 watt
replacement for	4 x Tl 60 cm
Ø diameter	200 mm
cut out	185mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands
T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



27018-1/2
LED panel Ø 225mm 18 watt
ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	1350
life time	50.000 hrs
beam angle	120 deg
wattage	18 watt
replacement for	4 x TI 60 cm
Ø diameter	225 mm
cut out	205mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

*Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.*

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands
T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



27020-1/2

LED panel Ø 240mm 20 watt

ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	1500
life time	50.000 hrs
beam angle	120 deg
wattage	20 watt
replacement for	4 x Tl 60 cm
Ø diameter	240 mm
cut out	220mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands

T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com



27025-1/2

LED panel Ø 300mm 25 watt

ww-nw



colour	ww-nw
power factor	>0.92
dimnable	Yes
led type	2835 SMD
voltage	85 -265vac
efficacy l/w	75-80 lm/w
total lumen	1850
life time	50.000 hrs
beam angle	120 deg
wattage	25 watt
replacement for	4 x T1 60 cm
Ø diameter	300 mm
cut out	276mm
height	13 mm
material	aluminium + frosted pvc
certificates	ce/rohs
warranty	2 years

Note

Specifications listed are in effect at time of printing and are subject to alteration without prior notice or obligation.
RAW LED reserves the right to periodically upgrade these specifications through additions, deletions and substitutions.

RAW LED B.V.

Hellingweg 134 | 2583 DX The Hague | The Netherlands
T +31(0)70 322 54 73 | F +31(0)70 358 41 80 | info@rawled.com | www.rawled.com